

HEATING PERFORMANCE DATA

Model	Heating		Outdoor conditions (DB)														
	Indoor Conditions DB		-22°F	-13°F	-4°F	0°F	5°F	10°F	17°F	20°F	25°F	32°F	35°F	40°F	47°F	50°F	57°F
			-30°C	-25°C	-20°C	-17.8°C	-15°C	-12.2°C	-8.3°C	-6.7°C	-3.9°C	0°C	1.7°C	4.4°C	8.3°C	10°C	13.9°C
ACIQ-09CC-HH-MB ACIQ-09ZPL-HP230B (208-230V)	60°F (15.6°C)	TC	7.75	8.99	9.98	10.40	10.93	11.94	13.15	13.26	13.44	13.55	13.81	14.04	14.34	14.74	15.08
		Input	1.74	1.76	1.67	1.64	1.59	1.72	1.88	1.78	1.69	1.58	1.51	1.39	1.31	1.27	1.23
	65°F (18.3°C)	TC	7.49	8.75	9.71	10.12	10.57	11.58	12.77	12.89	13.11	13.17	13.43	13.61	13.85	14.31	14.64
		Input	1.79	1.80	1.72	1.68	1.63	1.77	1.93	1.82	1.72	1.62	1.56	1.43	1.34	1.30	1.27
	70°F (21.1°C)	TC	7.28	8.46	9.40	9.85	10.22	11.21	12.40	12.55	12.69	12.84	13.00	13.25	13.49	13.84	14.16
	Input	1.83	1.85	1.76	1.72	1.68	1.82	1.98	1.86	1.76	1.67	1.59	1.47	1.37	1.34	1.30	
ACIQ-12CC-HH-MB ACIQ-12ZPL-HP230B (208-230V)	75°F (23.9°C)	TC	6.99	8.13	9.05	9.50	9.80	10.75	11.93	12.01	12.22	12.39	12.46	12.72	12.93	13.28	13.67
		Input	1.89	1.91	1.81	1.77	1.73	1.88	2.05	1.91	1.82	1.72	1.63	1.51	1.42	1.37	1.34
	60°F (15.6°C)	TC	8.84	10.19	11.19	11.72	12.29	13.49	14.86	15.15	15.31	15.58	15.89	16.21	16.44	16.82	17.22
		Input	1.95	1.91	1.84	1.76	1.73	1.70	1.70	1.68	1.66	1.66	1.64	1.43	1.22	1.18	1.17
	65°F (18.3°C)	TC	8.56	9.86	10.88	11.43	11.91	13.04	14.45	14.65	14.89	15.15	15.43	15.74	15.89	16.28	16.71
	Input	1.99	1.97	1.87	1.80	1.77	1.74	1.76	1.72	1.70	1.70	1.68	1.46	1.25	1.21	1.20	
ACIQ-18CC-HH-MB ACIQ-18ZPL-HP230B (208-230V)	70°F (21.1°C)	TC	8.31	9.56	10.62	11.10	11.54	12.71	14.02	14.27	14.51	14.78	15.05	15.28	15.48	15.84	16.25
		Input	2.04	2.01	1.91	1.86	1.82	1.79	1.79	1.77	1.75	1.73	1.50	1.29	1.25	1.22	
	75°F (23.9°C)	TC	8.01	9.21	10.21	10.71	11.03	12.24	13.39	13.71	13.96	14.19	14.39	14.66	14.89	15.24	15.57
		Input	2.11	2.07	1.96	1.92	1.88	1.84	1.84	1.84	1.80	1.79	1.77	1.55	1.32	1.28	1.26
	60°F (15.6°C)	TC	13.08	15.25	16.83	17.70	18.36	20.32	22.19	22.37	22.32	22.23	22.20	22.53	22.92	23.48	23.93
	Input	3.05	3.06	2.93	2.86	2.78	2.83	2.93	2.86	2.85	2.83	2.77	2.50	2.29	2.23	2.17	
ACIQ-24CC-HH-MB ACIQ-24ZPL-HP230B (208-230V)	65°F (18.3°C)	TC	12.71	14.86	16.42	17.24	17.92	19.69	21.54	21.66	21.69	21.62	21.57	21.91	22.19	22.75	23.25
		Input	3.12	3.16	2.99	2.92	2.86	2.90	2.99	2.94	2.91	2.89	2.85	2.56	2.35	2.27	2.23
	70°F (21.1°C)	TC	12.39	14.40	16.00	16.77	17.39	19.10	20.91	20.94	20.98	21.01	21.05	21.27	21.48	22.05	22.55
		Input	3.20	3.23	3.07	2.99	2.93	2.98	3.07	3.03	2.99	2.95	2.91	2.64	2.41	2.34	2.29
	75°F (23.9°C)	TC	11.83	13.75	15.41	16.16	16.73	18.26	20.18	20.13	20.20	20.11	20.29	20.53	20.66	21.19	21.76
	Input	3.29	3.34	3.16	3.07	3.01	3.07	3.15	3.13	3.09	3.05	3.01	2.73	2.49	2.41	2.35	
ACIQ-24CC-HH-MB ACIQ-24ZPL-HP230B (208-230V)	60°F (15.6°C)	TC	18.07	21.00	23.28	24.25	25.58	26.87	27.54	28.63	29.55	30.41	31.31	31.86	32.04	33.16	33.54
		Input	3.86	3.99	3.81	3.74	3.62	3.44	3.28	3.30	3.27	3.28	3.27	2.88	2.51	2.44	2.39
	65°F (18.3°C)	TC	17.57	20.48	22.63	23.66	24.76	25.99	26.87	27.69	28.80	29.53	30.31	30.84	31.16	32.03	32.56
		Input	3.97	4.09	3.92	3.81	3.71	3.53	3.37	3.38	3.36	3.35	3.37	2.95	2.57	2.51	2.46
	70°F (21.1°C)	TC	17.07	19.85	22.05	23.08	23.97	25.13	26.08	26.98	27.82	28.64	29.51	29.82	30.20	30.95	31.71
	Input	4.08	4.21	4.01	3.91	3.82	3.61	3.45	3.46	3.45	3.45	3.46	3.02	2.65	2.58	2.52	
ACIQ-24CC-HH-MB ACIQ-24ZPL-HP230B (208-230V)	75°F	TC	16.40	19.00	21.24	22.13	23.13	24.13	25.12	25.88	26.74	27.44	28.48	28.69	29.08	29.84	30.37
	(23.9°C)	Input	4.20	4.35	4.12	4.03	3.95	3.70	3.54	3.55	3.54	3.54	3.55	3.12	2.73	2.67	2.59

- LEGEND**
- DB --- Dry Bulb
 - WB --- Wet Bulb
 - TC --- Total Net Capacity (1000 Btu/hour)
 - Input --- Total Power (kW)
 - COP --- W/W