



Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left-hand refrigerant and plumbing connections, with downturn suction line for easy installation in manufactured housing applications.
- Downflow plates and manufactured housing drain hose included.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 - 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Liquid line Schrader valve for coil pressurization-confirmation testing.
- Heavy duty polypropylene drain pans.
- Drain connection: 177L pans have single LH 3/4" FPT, 195L pans have quad drains, 3/4" FPT.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Standard five-year limited parts warranty. Upgrades to an extended 10 year parts warranty with online registration.

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE R 410-A	DIMENSIONS			SHIPPING INFORMATION			
			PAN WIDTH (W)"	PAN DEPTH (D)"	COIL BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
ACiQ-2413UDPBCA	24,000	0.055	17-3/4	19-5/8	13-1/2	17	27	N/A	30
ACiQ-3617UDPBCA	36,000	0.068			17-1/2	23	36	47	25
ACiQ-3619UDXBCB					19-1/2	25	40	53	20
ACiQ-4821UDXBCA	48,000	0.080			21-1/2	N/A	45	60	16
ACiQ-4823UDXBCB				19-1/2	23-1/2		49	63	12
ACiQ-5919UDXBCA	60,000	0.089		19-1/2	19-1/2	34	54	70	

Notes: Use metal drain pan on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F.

BRAND	TONNAGE	COIL HEIGHT	CASED/UNCASED	CONFIGURATION	METERING	CABINET WIDTH	MATERIAL	Minor Design Sequence/ Series - Design Change
ACiQ	18 = 1.5 ton 24 = 2 ton 30 = 2.5 ton 36 = 3 ton 42 = 3.5 ton 48 = 4 ton 60 = 5 ton	13 = 13-1/2" 17 = 17-1/2" 19 = 19-1/2" 21 = 21-1/2" 23 = 23-1/2" 27 = 27-1/2"	U = Uncased C = Cased	M = Multiposition D = Downflow U = Upflow V = Vertical H = Horizontal	P = Piston/ Flowrator X = TXV E = EEV	A = 14" B = 17-1/2" C = 21" D = 24-1/2"	C = Copper D = Aluminum	A - Z

In keeping with its commitment to continuous improvement, ACiQ reserves the right to make changes without notice and incurring obligation.