



**HEATING PERFORMANCE**

Model	Outdoor Conditions DB	TC: Total Heating Capacity (BTU/hr)					PI: Power Input (kW)				
		Indoor Conditions DB (°F)					Indoor Conditions DB (°F)				
		60.8°F (16.0°C)	68°F (20.0°C)	70°F (21.1°C)	71.6°F (22.0°C)	75.2°F (24.0°C)	60.8°F (16.0°C)	68°F (20.0°C)	70°F (21.1°C)	71.6°F (22.0°C)	75.2°F (24.0°C)
<b>ACIQ-18W-HH-MD</b> <b>ACIQ-18ZPL-HP230C</b> (208-230V) Test Airflow/CFM: 635	-22°F (-30.0°C)	9595	9403	9356	9318	9234	1.91	1.93	1.93	1.93	1.94
	-13°F (-25.0°C)	12082	11841	11782	11735	11629	0.00	0.00	0.00	0.00	0.00
	-4°F (-20.0°C)	15435	15126	15050	14990	14855	0.00	0.00	0.00	0.00	0.00
	0°F (-17.8°C)	16853	16516	16433	16368	16220	0.96	0.97	0.97	0.97	0.97
	5°F (-15.0°C)	18626	18253	18162	18089	17927	2.16	2.17	2.18	2.18	2.19
	14°F (-10.0°C)	18513	18143	18052	17980	17818	2.41	2.43	2.43	2.43	2.44
	17°F (-8.3°C)	18475	18106	18015	17943	17782	2.49	2.51	2.51	2.52	2.53
	22°F (-5.6°C)	18406	18038	17948	17876	17715	2.36	2.38	2.39	2.39	2.40
	27°F (-2.8°C)	18337	17971	17881	17809	17649	2.23	2.25	2.26	2.26	2.27
	32°F (0.0°C)	18268	17903	17813	17742	17583	2.11	2.12	2.13	2.13	2.14
	35°F (1.7°C)	18227	17862	17773	17702	17543	2.03	2.05	2.05	2.06	2.06
	37°F (2.8°C)	18652	18278	18187	18114	17951	2.00	2.02	2.02	2.03	2.03
	42°F (5.6°C)	19713	19319	19222	19145	18973	1.93	1.94	1.95	1.95	1.96
	44.6°F (7.0°C)	20137	19735	19636	19558	19381	1.90	1.91	1.92	1.92	1.93
	47°F (8.3°C)	20774	20359	20257	20176	19994	1.85	1.87	1.87	1.88	1.88
	52°F (11.1°C)	20028	19627	19529	19451	19276	1.63	1.64	1.65	1.65	1.66
	57°F (13.9°C)	19282	18896	18801	18726	18558	1.40	1.42	1.42	1.42	1.43
59°F (15.0°C)	18983	18603	18510	18436	18270	1.31	1.33	1.33	1.33	1.34	
62°F (16.7°C)	18535	18164	18074	18001	17839	1.18	1.19	1.19	1.19	1.20	
64.4°F (18.0°C)	18237	17872	17783	17711	17552	1.09	1.10	1.10	1.10	1.11	

**LEGEND**  
 - TC: Total Cooling Capacity (BTU/hr)  
 - PI: Power Input (kW)  
 - DB: Dry Bulb  
 - WB: Wet Bulb