



Submittal Data Sheet

Indoor Unit Model#: ACiQ-36FM-HH-MD
Outdoor Unit Model#: ACiQ-36ZPL-HP230C

36K Ceiling & Floor Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

System Product Code: 810175551609
Indoor Unit Product Code: 810175551302
Outdoor Unit Product Code: 810175550985



INDOOR UNIT SPECIFICATIONS

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)		1224.3 / 1088.9 / 988.8 / 765.2 / 653.3
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)		NA / 51.0 / 45.5 / 39.0 / 35.0
Dimension (W×D×H)	inch	64.96 x 26.57 x 9.25
	mm	1650.0 × 675.0 × 235.0
Package (W×D×H)	inch	67.91 x 29.72 x 12.52
	mm	1725 × 755 × 318
Net/Gross Weight	lbs	88.85 / 104.94
	kg	40.3 / 47.6

OUTDOOR UNIT SPECIFICATIONS

Compressor Type		TWIN-ROTARY
Compressor Model		EKPQ420D1UMUA
Refrigerant		R454B
Refrigerant Oil Charge (mL)		1460
Refrigerant Oil		VG75
Outdoor Air Flow (Max) (CFM)		3001.9
Outdoor Noise Level (dBA)		65.0
Dimension (W×D×H)	inch	38.58 x 16.34 x 38.39
	mm	980.0 × 415.0 × 975.0
Package (W×D×H)	inch	45.08 x 19.68 x 42.52
	mm	1145 × 500 × 1080
Net/Gross Weight	lbs	206.57 / 237.44
	kg	93.7 / 107.7

EFFICIENCY RATINGS

Cooling		Heating	
SEER2	20	HSPF2-4	10.8
EER2	12.0	COP	3.29

COOLING PERFORMANCE

Cooling (Btu/hr)	
Rated Capacity	36400
Min/Max Capacity	6100~38300
Moisture Removal (L/h)	3.10
Standard Operating Range (°F/°C)	-22~122 (-30~50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

HEATING PERFORMANCE

Heating (Btu/hr)	
1. @ 47°F Rated	38000
1. @ 47°F Min/Max Capacity	11100~45400
2. @ 17°F Rated	30200
3. @ 5°F Rated: Capacity / COP	39500 / 2.02
3. @ 5°F Max: Capacity	39500
Standard Operating Range (°F/°C)	-22~75 (-30~24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB


ELECTRICAL SPECIFICATIONS

Power Supply	208/230V, 60Hz, 1Ph
System MCA	38.00
Connection Wiring	14#x3
System MOP	40
Compressor RLA	24.5
Outdoor Fan Motor RLA	2.1
Outdoor Fan Motor W	250
Indoor Fan Motor RLA	1.0
Indoor Fan Motor W	90
System Power Input @ Cooling (W)	3033 (590 ~ 3610)
System Power Input @ Heating (W)	3385 (675 ~4070)
MCA: Min. circuit amps (A)	MOP: Max. overcurrent protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

REFRIGERANT PIPING SPECIFICATIONS


Throttle type (Indoor)	N/A
Throttle type (Outdoor)	EXV+Throttle valve
Liquid Size	9.52mm (3/8in)
Gas Size	19mm (3/4in)
Max. Piping Length (ft/m)	246.00 (75)
Max. Height Difference (ft/m)	98.40 (30)
Max. Pre-charged Length (ft/m)	24.6 (7.5)
Refrigerant Pre-charged Amount (oz/kg)	126.99 (3.60)
Additional Charge of Refrigerant ((oz/ft)/(g/m))	0.32 (30)
Connection Method	Flared

Indoor Unit Dimensions




Model	A	B	C	D
18K/24K	42in(1068mm)	26-1/2in(675mm)	9-1/4in(235mm)	38-3/4in(983mm)
36K/48K/60K	65in(1650mm)	26-1/2in(675mm)	9-1/4in(235mm)	61-5/8in(1565mm)


Indoor Unit Installation Instructions



Outdoor Unit Dimensions



Outdoor Unit Installation Instructions



- ☒ Meets all spatial requirements shown in Installation Clearance Requirements above.

Features

- 2 Style Installation
- 3D Airflow
- Refrigerant leakage detection sensor
- Humidity sensor
- "88" display tube
- 1~100% fan speed setting
- WiFi capability: through WiFi dongle or wired controller with built-in WiFi
- OTA (by using WiFi dongle)
- 2-pin connector(HA/HB) for programmable wired controller
- Multiple control options available:
 - Two way communication wired controller: 120N (X6)
 - Two way communication wired controller with built-in WiFi: 120N (X6W)
 - Infrared wired controller: 120L
 - Wireless remote controller
 - Third-Party 24V Thermostat*

*24V interface is required.