

SUBMITTAL DATA SHEET

Heat Pump Water Heater System		50 Gallon
Location:	Approval:	
Engineer:	Date:	
Submitted to:	Construction:	
Submitted by:	Unit #:	
Reference:	Drawing #:	

Product Model

ACiQ-50G-HP-WH

Ceritified

AHRI

CUL

CUL

US

ENERGY STAR

SYSTEM PERFORMANCE DATA		
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	240V,1Ph,60Hz
Voltage Range	(V)	208~240
Electrical		
Minimum circuit ampacity	(A)	23.6A (208V) / 26.8A (240V)
Max.fuse	(A)	25A (208V) / 30A (240V)
Connection wiring	()	10AWG*3
Energy information		
Normal Gallon Capacity	(Gallon)	50
Rated Gallon Capacity	(Gallon)	47
Uniform Energy Factor (UEF)		3.75
First Hour Rating (FHR)	(Gallon)	69
Water Outlet Temperature Range	(Deg. °F)	109~149
Upper Element Wattage	(W)	4500 (240V)
Lower Element Wattage	(W)	4500 (240V)
Compressor capacity	(W)	1500
Total Unit Wattage (input)	(W)	5500
Cold Climate Efficiency (CCE)		3
Recovery In G.P.H. 90° F Rise		27.5
Heat pump ambient operating range	(Deg. °F)	37~109
Element ambient operating range	(Deg. °F)	5~115
Sound	(dBA)	49.5



UNIT DATA		
Unit Height	(inch)	66.4
Unit Diameter	(inch)	21.70
Unit Weight	(lbs)	218
Shipping Length	(inch)	28.3*27.2
Shipping Height	(inch)	74.8
Shipping Weight	(lbs)	264.6
Inlet Water Connection Size	(inch)	3/4
Outlet Water Connection Size	(inch)	3/4
Drainage Hose	(inch)	3/4
Installation Clearance (Back)	(inch)	0
Installation Clearance (Side)	(inch)	6
Installation Clearance (Top)	(inch)	20
Refrigerant Type		R134a
Refrigerant Charge	OZ	18.34
Loading Quantity (40 HQ)	pcs	51







