

## **Submittal Data Sheet**

Indoor Unit Model#: ACiQ-09W-E-M

9K R32 Wall Mounted Air Handler (For Multi-Zone Systems)			
Location: Approval:			
Engineer:	Date:		
Submitted to:	Construction:		
Submitted by:	Unit #:		
Reference:	Drawing #:		



INDOOR UNIT SPECIFICATIONS				
Indoor Fan Motor Output Power (W)		13		
Indoor Fan Airflow Volume (Turbo / Hi / Med / Lo)	Cooling Mode (CFM)	353 / 324 / 271 / 247		
	Heating Mode (CFM)	353 / 335 / 282 / 247		
Indoor Fan Speed (Turbo / Hi / Med / Lo)	Cooling Mode (rpm)	1130 / 980 / 920 / 850		
	Heating Mode (rpm)	1130 / 1030 / 940 / 850		
Indoor Noise Level (Turbo / Hi / Med / Lo)	Sound Pressure dB(A)	42 / 39 / 36 / 34		
Dimension (W×D×H)	inch	30.24 x 7.87 x 11.77		
	mm	768 x 200 x 299		
Package (W×D×H)	inch	32.72 x 11.10 x 14.61		
	mm	831 x 282 x 371		
Net/Gross Weight	lbs	16.53 / 22.05		
	kg	7.50 / 10.00		

COOLING PERFORMANCE			
Cooling (Btu/hr)			
Cooling Capacity*	9100		
Moisture Removal (L/hr)	0.7		
Indoor Temp. Operating Range °F(°C)	60.8°F ~ 89.6°F (16°C ~ 32°C)		

ELECTRICAL SPECIFICATIONS		
Power Supply (V, Hz, Ph)	208/230V, 60 Hz, 1 Ph	
Input Current (A)	0.20	
Recommended Connection Wiring (AWG)	4 x 18	

HEATING PERFORMANCE			
Heating (Btu/hr)			
Heating Capacity*	10000		
Indoor Temp. Operating Range °F(°C)	50°F ~ 89.6°F (10°C ~ 32°C)		

REFRIGERANT & PIPING SPECIFICATIONS		
Refrigerant Type	R32	
Liquid Side Pipe Diameter	1/4" (6.35 mm)	
Gas Side Pipe Diameter	3/8" (9.52 mm)	
Drainage Pipe Diameter	2/3" (16.90 mm)	
Connection Method	Flared	

<sup>\*</sup>Air handler is capable of performance figures & efficiency ratings listed above, actual performance is dependent on the efficiency of the condenser the air handler is paired with and the application/system it is

## Features

- Detachable lower panel and plate support to provide additional clearance during installation process
- New design allows for PCB to be easily access and does not requirer disassembly of the unit frame
- Unit equipped with a dust detection system that alerts user when the filter screen needs to cleaned
- Equipped with a strengthened mounting plate that includes a level to ensure accurate positioning and installation of the unit to the wall
- WiFi capability: through WiFi dongle or wired controller with built-in WiFi





