



Submittal Data Sheet

Indoor Unit Model#: AC-I-3036ACL-21

Outdoor Unit Model#: AC-I-36AC14

R32 36K 21" EVAPORATOR A-COIL & 36K TOP-DISCHARGE AC-COOLING ONLY CONDENSER

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

System UPC Product Code: 810175554204

A-Coil UPC Product Code: 810175554051

Outdoor Unit UPC Product Code: 810175554112



EFFICIENCY RATINGS

Cooling

SEER2	14.30
EER2	11.70

COOLING PERFORMANCE & OPERATING TEMPERATURE

Cooling (Btu/hr)

Rated Capacity	35000	
System Power Input (W)	3000	
Rated Current (A)	13.80	
Ambient Temperature Range (Cooling Operation)		
Indoor Unit	°F	60°F ~ 90°F
	°C	16°C ~ 32°C
Outdoor Unit	°F	5°F ~ 131°F
	°C	-15°C ~ 55°C

ELECTRICAL SPECIFICATIONS

Indoor Power Supply	220-230V, 1Ph, 60Hz
Outdoor Power Supply	208/230V, 1 Ph, 60Hz
Voltage Range (V)	187 ~ 253
Outdoor MCA (A)	24
Outdoor MOP (A)	30
MCA: Min. circuit amps (A)	MOP: Max. overcurrent protection (A)

EVAPORATOR A-COIL SPECIFICATIONS

Dimension (W×D×H)	inch	21.02 x 21.02 x 23.58
	mm	534 x 534 x 599
Package (W×D×H)	inch	24.80 x 27.36 x 25.98
	mm	630 x 695 x 660
Net/Gross Weight	lbs	64.0 / 74.0
	kg	29.2 / 33.6


OUTDOOR UNIT SPECIFICATIONS

Compressor Type		Rotary
Compressor Model		KSG280N1VMT
Compressor Capacity (W)		10530
Compressor Input (W)		2415
Compressor Rated Current RLA (A)		11.8
Refrigerant Oil Type		Ester Oil VG75
Refrigerant Oil Charge (mL)		850
Outdoor Noise Level (dBA)		59
Outdoor Airflow (CFM)		2650
Outdoor Fan Motor Qty.		1
Outdoor Fan Motor Input (W)		200
Outdoor Fan Motor RLA (A)		0.92
Dimension (W×D×H)	inch	29.13 x 29.13 x 25.00
	mm	740 x 740 x 635
Package (W×D×H)	inch	30.32 x 30.32 x 26.18
	mm	770 x 770 x 665
Net/Gross Weight	lbs	145.0 / 154.0
	kg	65.9 / 70.0
RLA: Rated Load Amps		W: Watts

REFRIGERANT & PIPING SPECIFICATIONS



Throttle type (Indoor)		TXV for Cooling
Refrigerant Type		R32
Refrigerant Charge	oz	79.37
	kg	2.25
Additional Charge of Refrigerant	oz/ft	0.52
	g/m	48.0
Liquid Side	in	3/8"
	mm	9.53
Gas Side	in	3/4"
	mm	19.05
Max. Piping Length	ft	131
	m	40
Max. Height Difference	ft	82
	m	25
Drainage Water Pipe Diameter (O.D.)	in	3/4"
	mm	19.05 mm
Connection Method	Indoor Unit	Braze
	Outdoor Unit	Flare to Braze

EVAPORATOR A-COIL DIMENSIONS



Model	18K/24K A-Coil 17.5"		30K/36K A-Coil 17.5"		30K/36K A-Coil 21"	
Dimensions	inch	mm	inch	mm	inch	mm
A	17-1/2	445	17-1/2	445	21	534
B	18	457	23-1/2	599	23-1/2	599
C	16-2/5	416	16-2/5	416	19-3/4	505
Model	48K/60K A-Coil 21"		48K/60K A-Coil 24.5"			
Dimensions	inch	mm	inch	mm		
A	21	534	24-1/2	622		
B	27-4/5	706	27-4/5	706		
C	19-3/4	505	23-2/5	594		

OUTDOOR UNIT DIMENSIONS



Dimensions \ Model		18K/24K		30K/36K		42K/48K/60K	
		inch	mm	inch	mm	inch	mm
W	Model width	23-5/8	600	29-9/64	740	29-9/64	740
L	Model length	23-5/8	600	29-9/64	740	29-9/64	740
H	Model height	25	635	25	635	32-7/8	835
A	Liquid side valve height	2-31/64	63	2-31/64	63	2-31/64	63
B	Distance between two valves	3-1/32	77	3-1/32	77	3-1/32	77
C	Gas side valve height	2-9/32	58	2-9/32	58	2-9/32	58